

WL 2000

An economical and effective POU cooler dispensing safe, clean drinking water for the workplace without the hassle of bottles. Ideal for small offices and factories, the WL2000 uses direct chill point-of-dispense technology to cool water directly from the mains supply. Our carbon filtration system means it tastes beautiful too so quality and safety are guaranteed.

Simply put, Great Water

Three Steps to Greatness

This Waterlogic dispenser has 3 core technologies which mean that what you get out of your machine is much better than what goes in:



1. Filtration: our filtration technology is really good at taking the bad stuff out and leaving the good stuff in. This stage removes chlorine and other water-borne tastes and odors.



2. Direct Chill: next, direct chill technology cools the water. A tube with refrigerant gas runs in a spiral alongside the water tube, chilling it to 5C or 12C.



3. BioCote®: we've got the inside covered and the outside too. As another layer of defense, BioCote keeps the dispensing area free of bacteria.









Performance Worthy of an Encore

- Constant fresh, pure water from direct chill technology to refresh and invigorate
- Ideal capacity for the small workplace
- Hot, cold and ambient options
- Easy connection to your existing mains water supply
- Value-for-money entry-level model
- Smart design with simple buttons and icons for ease of use
- Freestanding and counter top options to suit every workplace
- Available with work surface top - ideal for coffee machines
- Sleek modern look improves office environment



The Boring Bits

Water Options	Technical Features	
<ul style="list-style-type: none"> •  •  •  	Type available	Freestanding Counter top
	Freestanding dimensions	W 345mm x H 1020mm x D 365mm W 13.6in x H 40.2in x D 14.4in
	Counter top dimensions	W 345mm x H 485mm x D 365mm W 13.6in x H 19.1in x D 14.4in
	Dispense area height	215mm, 8.5in
Symbols	Weight	Freestanding: 24KG Counter Top: 22KG
 Ambient water	Standard filtration supplied (where applicable)	1 x Carbon Block (CBC) or 1 x Granular Activated Carbon (GAC)
 Cold water	Additional features	Leak detection
 Hot water	Capacity	Hot tank: 1.5 liters (0.396 US gal.)
	Compressor	230V (or 110v) /50Hz compressor
	Water temperatures	Cold: 5°C/41°F Hot: 87°C/189°F

Tested and Certified



Waterlogic International Limited and WLI Trading Limited reserve the right, in order to reflect continuous research and development, to amend or change specifications without prior notice. Waterlogic and the Waterlogic logo, Firewall and the Firewall logo are trademarks in countries where the Group operates. WLT Trading Ltd licensed to use BioCote, and BioCote logo which are registered trademarks of BioCote Ltd.

Speak to a Water Expert

USA, Canada and Mexico
info@waterlogicausa.com
 + 1 402 884 7212

Waterlogic USA,
 11710 Stonegate Circle,
 Omaha, NE 68164

Rest of the world
exportsales@waterlogic.com
 + 353 1 293 1960

WLI Trading Ltd.
 Suite 4, 2nd Floor Beacon Court,
 Sandyford, Dublin 18, Ireland
www.waterlogic.com

Visit Waterlogic

